



REV	DATE	DESCRIPTION
A	06/13/"07	#033-307
B	10/12/"09	Official Drawing
C	07/06/"12	Add P/N

Note:

1.Material:

- 1.1 Insulator: P.B.T UL 94-V0 rated.
- 1.2 Contact: Brass,t=0.20mm.
- 1.3 Shell: Cold rolled steel,t=0.30mm.

2.Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000 MΩ Min at DC 500V.
- 2.5 Temperature range: -55°C~+105°C

3.Finishes:

- 3.1 Contacts:Gold flashed 1u",3u",5u",10U",15u",30u".
- 3.2 Shell: Nickel plated.



FU-YAO TECHNOLOGY CO., LTD.

復堯科技股份有限公司

MODEL NAME:

USB B SOLDER TYPE MALE

MARK EXPLAIN:

△:Revision Change

[1]:Important Dimension

①:Note

TOLERANCE:

0.000: ±0.10

0.00: ±0.20

0.0: ±0.30

0.:

ANGLE: ±1.0°

UNIT: mm

PART NO. USBB-04PCWAAAB0

APPROVED BY:

CHECKED BY:

DRAW BY: ALAN

FILE NO.FIG01827

SCALE: FREE

DATE: 960613