

HALF PITCH PIN TYPE FOR SOLDER

HALF PITCH



Material & finish

SHELL:
Steel
Nickel plated steel

PIN CONTACT:
Phosphor bronze
Gold plated



INSULATOR:
PBT & Glass-fibre reinforced UL 94-V0

CURRENT RATING:
1 Amp

DIELECTRIC STRENGTH:
500V for one minute

INSULATOR RESISTANCE:
500M Ω Min.(at 500V DC)


TEMPERATURE:
-55° C to +105° C



MALE

MALE

NO OF CONTACTS	A	B
26	24.00	19.85
50	39.30	34.85
68	50.80	46.35



FEMALE

FEMALE

NO OF CONTACTS	A	B	C
26	24.00	19.46	9.3
36	30.40	25.80	8.4
50	39.20	34.70	9.3
68	50.70	46.20	9.3

ORDERING INFORMATION

MD1 - XX X K X A X X X 0 0 0 0

TYPE
MD1: 1.27 PIN TYPE
SOLDER FOR ROUND
CABLE

No. OF CONTACTS
14 ~ 100

CONTACT TYPE
P: PLUG
S: SOCKET

INSULATOR COLOR
K: BLACK

SPECIAL FUNCTION
C: WITH LATCH
L: WITH #2-56 SCREW

COVER OD:
6~14mm

COVER TYPE:
A: NO COVER
I: PLASTIC COVER
M: METAL COVER

SHELL PLATING
A: NICKEL

CONTACT PLATING
A: GOLD FLASH
E: 15u"
F: 30u"