
RoHS COMPLIANT

REV	DATE	DESCRIPTION
B	03/07/"14	#063-1 Add P/N



MATERIALS:

Housing And Cover:	PBT+Glass Fiber UL94V-0, Black
Contacts:	Phosphor Bronze Gold Selective Plated
Back Shell:	Zinc Alloy,Nickel Plated Over Copper
Shell:	Steel,Nickel Plated Over Copper
Jackscrew:	Steel,Nickel Plated Over Copper
Cable Clipper:	Steel,Nickel Plated Over Copper
Flat Screws:	Steel,Nickel Plated Over Copper

ELECTRICAL CHARACTERISTICS:

Contact Currect Rating:	1 Amp
Dielectric Withstanding Voltage:	250V AC
Insulation Resistance:	>500MΩ/Min
Contact Resistance:	35mΩ/Max
Operation Temperature:	-55°C ~ +105°C

WIRE HOLDER:
0.61mm OR 0.68mm

ENTRY HOLE SIZE:
ø9.0 OR ø11.0

FU-YAO TECHNOLOGY CO., LTD.
復堯科技股份有限公司

MODEL NAME:
VHDCI PITCH 0.8mm 68P CABLE PLUG CONNECTOR I.D.C. ASSEMBLY TYPE 30u"

MARK EXPLAIN:
⚠:Revision Change
1:Important Dimension
①:Note

TOLERANCE:
0.000:
0.00 : ±0.15
0.0 : ±0.25
0. : ±0.30
ANGLE: ±3.0°
UNIT: mm

PART NO. MC2-68MKFAMXV0Ax
APPROVED BY:
FILE NO. FIG01966-1
CHECKED BY:
SCALE: FREE
DRAW BY: LEE
DATE : 980609